



**Sales / Service:**

3305 Airport Circle  
 Pittsburg, KS 66762  
 P: 620-235-1712  
 F: 620-235-1772  
 sales@apexstages.com  
[www.apexstages.com](http://www.apexstages.com)

**Sales Representative:**

Jeff Hess  
 Progressive Products, Inc.  
 C: 417-438-0213  
[jeff@progressiveproductsinc.com](mailto:jeff@progressiveproductsinc.com)



**APEX 5040**

**Mobile Hydraulic Stage** Proudly Made in the USA



**Specifications:**

**Trailer:**

Trailer Length 53'  
 Trailer Width 102"  
 Trailer Height 13'3"  
 Trailer Weight 55165#  
 Rear Axle Rating 20000#  
 Front Axle Rating 20000#

**Stage Deck:**

Floor Size 50' x 38'6"  
 Floor Height 4'-6"  
 Floor Rating 150#/sq ft  
 Structure Marine Plywood/Alum  
 Floor Support 40-7000# jacks  
 Outrigger Vert Travel 27"  
 Outrigger Lift Cap. 25000# ea

**Stage Roof:**

Covered Roof 52'10"x 39'6"  
 Deck to Center I-beam 29'6"  
 Surface Fiberglass/Alum  
 Roof Capacity 32000#  
 Max Height Deck-Glass 32'3"  
 Max Height Speaker Cable 47' 2"  
 Fly Bay Capacity 6000# ea side  
 Front/Rear I-beams 6000# ea.  
 Center I-beam 7000# ea.  
 Speaker Wing-Wing 65'11"

**Other:**

Install Time 1-2 hours  
 Site Prep None  
 Hauling Mode Tractor Trailer  
 Power Source 20hp Honda Motor  
 Front Axle to Kingpin 29'11"  
 Front Axle to Rear Axle 10'1"  
 Hyd Pump Capacity 3.0 gpm  
 Hyd Pump Max Press 4000 psi  
 Hyd Oil Capacity 40 gal  
 Speaker wings either side



The APEX 5040 features a 50' wide x 40' deep x 30' tall stage area and is built on five non-slip floor sections. A center section built on the trailer frame, and a bi-folding two part deck on either side. The roof structure is capable of supporting a maximum of 44,000 lbs. The fly-bays have a capacity of 6,000 lbs. each and are designed to facilitate virtually every line array on the market. The trailer frame is supported at six points by hydraulic controlled leveling outriggers. These out-riggers allow the deck to be set between 4' and 6' high in order to adapt to most terrain and venue requests. Additional features include, California legal split axes, and the ability to carry approximately 4,000 lbs. of extra equipment inside the cargo area.

You decide which side of the stage is "upstage" and which is "downstage" by proper placement of the two taller corner towers. The 6" differential in height allows for drainage away from the front of the stage.

**Contact us for a quotation today!**

